

GE® Indoor Tankless Water Heater



Model# GN94DNSRSA



FEATURES

Control Type	Integrated Electronic LED
Fuel Type	Natural Gas (factory set)
Ignition System	Direct Electronic Ignition
South Coast Air Quality Management District	Yes
Heat System	Demand Activate Technology
Overheat Protection System	Yes
PreciseTemp	+/- 3°F
Temperature Setting Memory	Yes
Vent	Concentric
Vent Cut-Out	5" Diameter
Combustible Air	No Roomsize Limitations
Mounting Location	Stud or Masonry Wall
Power Cord Length	6' (3-Prong) Included
Condensate Collector	Integrated (tubing not included)

- - Continuous Hot Water*
- Energy Savings - Save up to 25% annually on your water heating bill*
- Compact Design - Frees up floor space with wall-mounted installation
- Installation Flexibility - Can be wall-mounted in many areas of the home
- Helps To Avoid Carbon Emissions - Up to 25% tied to your water heating compared to a standard 40-gallon gas tank model based on DOE testing
- Demand-Activated Technology - Only heats the water when needed
- - **Compared to a standard 40-gallon gas tank model based on 2007 fuel costs per DOE testing
- - *Flow rates may diminish based on simultaneous use of multiple shower/baths and/or appliances
- - A Product of Ecomagination
- Freeze Protect - Protects your water heater from freezing at temperatures that can drop as low as -30 degrees F
- PreciseTemp - Within +/- 3 degrees F

Have more questions? Please contact 1-800-626-2005

GE® Indoor Tankless Water Heater



Model# GN94DNSRSA

APPROXIMATE DIMENSIONS (HxDxW)

- 22 7/8 in x 9 13/16 in x 14 in

CAPACITY

- Max Flow Rate Capacity (GPM) @ 35°F Rise 9.4
- Max Flow Rate Capacity (GPM) @ 77°F Rise 4.3
- Unit Capacity Indoor Compact

Claims & Certifications

- ENERGY STAR® Qualified

WARRANTY

- Parts Warranty - Limited 5-year entire appliance
Limited 10-year heat exchanger
- Labor Warranty - Limited 1-year entire appliance
- Warranty Notes - See written warranty for full details

Have more questions? Please contact 1-800-626-2005